



COMPILARE A CURA DEL CLIENTE TO BE SPECIFIED BY CUSTOMER

| | |
|---|--|
| AMBIENT TEMPERATURE MIN/MAX °C | |
| CONTROLLED OPERATING TEMPERATURE °C | |
| UNCONTROLLED (SELF LIMITING) OPERATING TEMPERATURE °C | |
| HEATED LENGTH (L) mm | (A) mm |
| SENSOR TYPE: PT100/RTD <input type="checkbox"/> T/C J <input type="checkbox"/> T/C K <input type="checkbox"/> | |
| SENSOR POSITION (B) mm INTO THE SAMPLE LINE | |
| SAMPLE TUBE PTFE <input type="checkbox"/> PFA <input type="checkbox"/> 316L <input type="checkbox"/> | |
| SAMPLE TUBE I.D./O.D. 4/6 <input type="checkbox"/> 4,35/6,35 <input type="checkbox"/> 6/8 <input type="checkbox"/> 8/10 <input type="checkbox"/> 10/12 <input type="checkbox"/> | |
| REPLACEABLE SAMPLE TUBE I.D./O.D mm | |
| NUMBER OF HEATED SAMPLE TUBE (MAX 3 TUBES) | |
| CALIBRATION TUBE (OPTION) PTFE <input type="checkbox"/> PFA <input type="checkbox"/> I.D./O.D mm | |
| BENDING RADIUS mm | |
| POWER LEADS mm | |
| MAX OPERATING PRESSURE bar | |
| POWER SUPPLY V | <input type="checkbox"/> SINGLE PHASE W/m..... |
| POWER SUPPLY V | <input type="checkbox"/> 3 PHASE W/m..... |
| THERMAL INSULATION <input type="checkbox"/> CLOSED CELLS SILICONE SPONGE | |
| <input type="checkbox"/> POLYESTER FELT | |
| <input type="checkbox"/> GLASS FIBRE FELT | |

| REV. | CHANGE | DATE | VERIFIED | DRAWN UP |
|------|--------|----------|----------|----------|
| 1 | REV | 05/04/19 | | |
| 2 | REV | 25/02/20 | | |
| | | | | |
| | | | | |

RACO
NOVATE MILANESE (MI)
ITALY
info@racosas.com

Property of RACO sas no reproduction allowed.
Proprietà RACO sas riproduzione vietata.

| | |
|-------|-----------------------------|
| TITLE | HEATED SAMPLE GAS LINE IP65 |
| ORDER | CUSTOMER |

| | | | |
|-------|---|----------|-------|
| SHEET | 1 | DOC NO | |
| NEXT | 0 | DWG/FILE | 1_1.1 |
| SCALE | | | |